



# Low Level Traffic Barrier

This is the most popular product in the Traffic segregation range and comprises of a single 200mm Rail with an impact height of 300mm. Standard Post centres are 1.6m and it has an overall height of 400mm. This fully module system can be made up to suit your needs and can be integrated with bollards and Pedestrian rail attachment.



## Applications and Benefits

Ideal for use around medium sized counter balance trucks with standard wheel arch so as the impact height matches the barrier. Low Level Traffic barrier is the perfect way to avoid unnecessary damage to your property. It will protect walls, building supports, valuable machinery and vulnerable equipment by repelling wayward vehicles. It offers real delineation of vehicles and clearly segregates traffic routes with a physical barrier you can trust.



## Customer Endorsement



“The barrier also has the added advantage of that as claimed it is a ‘flexible’ barrier. We can easily replace it to suit any situation or site update and it has already been used to great effect as a vehicle reversed into a section of barrier with no damage caused to the vehicle or barrier due to the forgiving ‘flexible’ nature of your product.”

*John Wilson, BOC Gases, Derby*



## Health and Safety Did You Know

“Employers must check to see whether the site has well-defined traffic routes that are free from obstructions, and that have firm and even surfaces.”

*(Workplace transport safety, An employers' guide)*



## Technical Did You Know

- Low level traffic barriers have been tested with an impact force of 152kN as set out in BS6399. This is the equivalent of a 1.5 tonne vehicle travelling at 10 miles per hour at a 90° impact.
- Impact height of 300mm (Low level)
- Ideal for medium sized Counter balance trucks or other equivalent vehicles.



Protecting People



Property



Profits



and the environment



A-Safe (UK) Ltd, Shay Lane, Halifax, W. Yorkshire, England HX3 6RL  
t: +44 (0)1422 344402 f: +44 (0)1422 323533 e: sales@asafe.com

[www.asafe.com](http://www.asafe.com)